

SL

2 / 3 / 4



Tomorrow's technology available today



Tomorrow's technology available today

The SL mower is rugged, compact and of low construction. Ideal for young plantations with low-hanging fruit. The new precision control allows accurate and gentle sensing of the tree trunk which cannot be damaged thanks to the rubber armoring of the swing disk. The swing arm is hydraulically or electrically positioned from the tractor using a controller or electric switcher.



Fix disc with precision sensor



SL front mounting with fix swing wing disc and self supply pump and tank



Hydraulic linear adjustment



Hydraulic outreach, hydraulic and automatic precision sensing and own oil supply (pump / tank)



SL front mounting with parallelogram displacement



Self supply pump and tank

Mod.														
		fix	mob.			HP	KG	A	B	C	D	E	F	
SL2/125-170	2	2	2	40-80	390	126	125	90	28	175	170	125	170	63/63 00/135+60 70/70
SL2/140-190*	2	2	2	40-80	420	141	130	90	28	195	175	140	190	00/145+60 80/80
SL2/160-210*	2	2	2	40-80	450	161	135	90	28	215	180	160	210	00/170+60 85/95
SL3/180-230	3	3	2	40-80	490	181	125	90	28	235	170	180	230	00/190+60 85/115
SL3/200-250*	3	3	2	40-80	520	201	130	90	28	255	175	200	250	00/210+60 95/135
SL3/230-280*	3	3	2	40-80	550	235	135	90	28	285	180	230	280	00/230+60 135/135
SL4/270-320*	4	4	2	40-80	600	271	130	90	28	325	175	270	320	45/225+60 155/155
SL4/310-360*	4	4	2	40-80	660	311	135	90	28	385	180	310	360	65/245+60 167/200
SL4/360-410*	4	4	2	40-80	750	367	155	90	28	435	225	360	410	77/290+60

*with the swinging disc D.800 the cutting width increase further 20cm